

KERN CM150-1N

Pocket scale with integrated calculator



Measuring system

Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	200 mg
Linearity:	200 mg
Readability [d]:	100 mg
Recommended adjusting weight:	100 g (M3)
Repeatability:	100 mg
Resolution:	1500
Stabilisation time under laboratory conditions:	2 s
Tare range:	150 g
Warm up time:	10 min
Weighing capacity [Max]:	150 g
Weighing system:	Strain gauge
Weighing units:	tl (Tw) tol g

Display

Display digit height (large):	1,200 cm
-------------------------------	----------

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

Power supply

Battery:	2x1.5 V AAA
Operating time:	33 h

Services (optional)

Adjustment at the location of installation: 961-247

DAkkS Certificate: 963-127

Category

Brand:	KERN
Category:	Balances
Product Group:	Pocket balance

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	205 x 136 x 32 mm
Gross weight:	313 g
Net weight:	165 g
Shipping method:	Parcel service

Construction

Casing material:	Plastic
Dimensions housing (WxDxH):	85 x 130 x 25 mm
Material weighing plate:	Plastic
Weighing surface (WxD):	70 x 80 mm

Piktogramme

STANDARD



OPTION



KERN CM1K1N

Pocket scale with integrated calculator



Measuring system

Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	2 g
Linearity:	2 g
Readability [d]:	1 g
Recommended adjusting weight:	1 kg (M3)
Repeatability:	1 g
Resolution:	1000
Stabilisation time under laboratory conditions:	2 s
Tare range:	1 kg
Warm up time:	10 min
Weighing capacity [Max]:	1 kg
Weighing system:	Strain gauge
Weighing units:	tl (Tw) tol g

Display

Display digit height (large):	1,200 cm
-------------------------------	----------

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

Power supply

Battery:	2x1.5 V AAA
Operating time:	33 h

Services (optional)

Adjustment at the location of installation: 961-247

DAkkS Certificate: 963-127

Category

Brand:	KERN
Category:	Balances
Product Group:	Pocket balance

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	137 x 204 x 32 mm
Gross weight:	318 g
Net weight:	188 g
Shipping method:	Parcel service

Construction

Casing material:	Plastic
Dimensions housing (WxDxH):	85 x 130 x 25 mm
Material weighing plate:	Plastic
Weighing surface (WxD):	70 x 80 mm

Piktogramme

STANDARD



OPTION



KERN CM320-1N

Pocket scale with integrated calculator



Measuring system

Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	200 mg
Linearity:	200 mg
Readability [d]:	100 mg
Recommended adjusting weight:	200 g (M3)
Repeatability:	100 mg
Resolution:	3200
Stabilisation time under laboratory conditions:	2 s
Tare range:	320 g
Warm up time:	10 min
Weighing capacity [Max]:	320 g
Weighing system:	Strain gauge
Weighing units:	tl (Tw) tol g

Display

Display digit height (large):	1,200 cm
-------------------------------	----------

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

Power supply

Battery:	2x1.5 V AAA
Operating time:	33 h

Services (optional)

Adjustment at the location of installation: 961-247

DAkkS Certificate: 963-127

Category

Brand:	KERN
Category:	Balances
Product Group:	Pocket balance

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	140 x 200 x 30 mm
Gross weight:	318 g
Net weight:	216 g
Shipping method:	Parcel service

Construction

Casing material:	Plastic
Dimensions housing (WxDxH):	85 x 130 x 25 mm
Dimensions of weighing plate (WxDxH):	70 x 80 x 20 mm
Material weighing plate:	Plastic
Weighing surface (WxD):	70 x 80 mm

Piktogramme

STANDARD



OPTION



KERN CM60-2N

Pocket scale with integrated calculator



Measuring system

Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	20 mg
Linearity:	30 mg
Readability [d]:	10 mg
Recommended adjusting weight:	50 g (M2)
Repeatability:	20 mg
Resolution:	6000
Stabilisation time under laboratory conditions:	2 s
Tare range:	60 g
Warm up time:	30 min
Weighing capacity [Max]:	60 g
Weighing system:	Strain gauge
Weighing units:	tl (Tw) tol g

Display

Display digit height (large):	1,200 cm
-------------------------------	----------

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

Power supply

Battery:	2x1.5 V AAA
Operating time:	33 h

Services (optional)

Adjustment at the location of installation: 961-247

DAkkS Certificate: 963-127

Category

Brand:	KERN
Category:	Balances
Product Group:	Pocket balance

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	135 x 205 x 32 mm
Gross weight:	306 g
Net weight:	180 g
Shipping method:	Parcel service

Construction

Casing material:	Plastic
Dimensions housing (WxDxH):	85 x 130 x 25 mm
Dimensions of weighing plate (WxDxH):	70 x 80 x 18 mm
Material weighing plate:	Plastic
Weighing surface (WxD):	70 x 80 mm

Piktogramme

STANDARD



OPTION

