

KERN TG1250-0.1FN

Premium measuring devices for paint coating, lacquer coating etc.



Category

| | |
|----------------|-------------------------|
| Brand: | Sauter |
| Category: | Coating thickness |
| Product Group: | Coating thickness gauge |

Packaging & shipping


| | |
|-------------------------------|-------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 250 x 198 x 50 mm |
| Gross weight: | 750 g |
| Net weight: | 90 g |
| Shipping method: | Parcel service |

Construction

| | |
|-------------------------------------|------------------|
| Cable length: | 1 m |
| Casing material: | Plastic |
| Dimensions (WxDxH): | 126 x 65 x 35 mm |
| Dimensions housing (WxDxH): | 130 x 64 x 32 mm |
| Overall dimensions mounted (WxDxH): | 130 x 64 x 32 mm |

Piktogramme

STANDARD



OPTION



Measuring system

| | |
|--|--------------------|
| Measuring range [Max]: | 100 x 1250 μ m |
| Minimal base thickness: | 300 μ m |
| Precision (of [Max]): | 3 % |
| Precision (Offset-Accur): | 1 % |
| Readability [d]: | 0 x 0,001 mm |
| Smallest sample surface, convex (radius): | 1,500 mm |
| Smallest sample surface, concave (radius): | 2,500 cm |
| Weighing units: | μ m inch (mil) |

Display

| | |
|-------------------------------|------|
| Display digit height (large): | 1 cm |
|-------------------------------|------|

Functions

| | |
|-----------------------|-----|
| Statistical function: | yes |
|-----------------------|-----|

Environmental conditions

| | |
|--------------------------------|-------|
| Maximum operating temperature: | 50 °C |
| Minimum ambient temperature: | 0 °C |

Power supply

| | |
|-----------------|-------------|
| Battery: | 2x1.5 V AAA |
| Operating time: | 50 h |

Services (optional)

| | |
|----------------------------------|---------|
| Factory calibration certificate: | 961-112 |
|----------------------------------|---------|