

Digital microscope sets KERN OZL-S



The flexible, affordable all-rounder with zoom function as a digital solution for schools, training companies, inspection authorities and laboratories

Features

- The flexible, cost-effective OZL-46 range is now also available to you as a comprehensive digital solution for your live investigations. Optionally available with an mounted tablet or C-mount camera. Naturally, the appropriate C-mount adapter is included with the delivery.
- The mounted KERN ODC 241 tablet-camera has been specially developed for simple, convenient and direct investigation of the sample on the screen. Ideally suited for school pupils and students in education or for demonstration purposes in the laboratory
- The mounted C-mount camera is available in different versions and can be used anywhere

- For detailed information on the individual components, see the relevant product description of the individual item
- A protective dust cover, eye cups, as well as multi-lingual user instructions are included in the scope of the delivery

Technical data

- Optical system: Greenough optics
- Brightness adjustable (separate)
- Tube 45° inclined
- Magnification ratio: 6,4:1
- Light distribution 50:50
- Interpupillary distance 55 - 75 mm
- Diopter adjustment: Both-sided
- Overall dimensions W×D×H 300×240×420 mm
- Net weight approx. 5 kg
- Eyepiece: HWF 10×/∅ 20 mm
- Field of view: ∅ 28,6 - 4,4 mm
- Objective: 0,7× - 4,5×
- Stand OZL 464/466: Pillar style
- Stand OZL 468: Arm curved
- Illumination: 3 W LED (incident + transmitted)

Model	Standard configuration (camera)				
	Included camera	Resolution camera	Interface	Sensor	Details microscope, camera
KERN					
OZL 464C825	ODC 825	5 MP	USB 2.0 (6,8 - 55 FPS)	CMOS 1/2,5"	KERN Optics catalogue Page 46, 85
OZL 466C825					
OZL 468C825					
OZL 464C832	ODC 832	5 MP	USB 3.0 (14,2 - 101,2 FPS)	CMOS 1/2,5"	
OZL 466C832					
OZL 468C832					
OZL 464T241	ODC 241	5 MP	WLAN, USB 2.0, HDMI, SD (15 - 30 FPS)	CMOS 1/2,5"	KERN Optics catalogue Page 46, 89
OZL 466T241					
OZL 468T241					

Pictograms

360° rotatable microscope head	Fluorescence illumination for compound microscopes With 3 W LED illumination and filter	USB 3.0 digital camera For direct transmitting of the picture to a PC
Monocular Microscope For the inspection with one eye	Phase contrast unit For a higher contrast	WLAN data interface For transmitting of the picture to a mobile display device
Binocular Microscope For the inspection with both eyes	Darkfield condenser/unit For a higher contrast due to indirect illumination	HDMI digital camera For direct transmitting of the picture to a display device
Trinocular Microscope For the inspection with both eyes and the additional option for the connection of a camera	Polarising unit To polarise the light	PC software To transfer the measurements from the device to a PC
Abbe Condenser With high numerical aperture for the concentration and the focusing of light	Infinity system Infinity corrected optical system	Automatic temperature compensation For measurements between 10 °C and 30 °C
Halogen illumination For pictures bright and rich in contrast	Zoom magnification For stereomicroscopes	Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram cf. DIN EN 60529:2000-09, IEC 60529:1989+A1:1999+A2:2013
LED illumination Cold, energy-saving and especially long-life illumination	Auto-focus For automatic control of the focus level	Battery operation Ready for battery operation. The battery type is specified for each device.
Incident illumination For non-transparent objects	Parallel optical system For stereomicroscopes, enables fatigue-proof working	Battery operation rechargeable Prepared for a rechargeable battery operation
Transmitting illumination For transparent objects	Integrated scale In the eyepiece	Plug-in power supply 230V/50Hz in standard version for EU. On request GB, AUS or USA version.
Fluorescence illumination For stereomicroscopes	SD card For data storage	Integrated power supply unit Integrated in microscope. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.
Fluorescence illumination for compound microscopes With 100 W mercury lamp and filter	USB 2.0 digital camera For direct transmitting of the picture to a PC	Package shipment The time required to manufacture the product internally is shown in days in the pictogram.

Abbreviations

C-Mount Adapter for the connection of a camera to a trinocular microscope	LWD Long Working Distance	SWF Super Wide Field (Field number at least \varnothing 23 mm for 10 \times eyepiece)
FPS Frames per second	N.A. Numerical Aperture	W.D. Working Distance
H(S)WF High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)	SLR camera Single-Lens Reflex camera	WF Wide Field (Field number up to \varnothing 22 mm for 10 \times eyepiece)

Your KERN specialist dealer: