

KERN OBE121

Elegant, dynamic and impressive - the new all-round compound microscope for schools, training and laboratories

KERN®



Piktogramme

STANDARD



OPTION



Power supply

Input voltage:	100 V - 240V AC 50/60Hz 0.3A
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO

Category

Brand:	Optics
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	425 x 340 x 245 mm
Gross weight:	5,500 kg
Net weight:	4,488 kg
Shipping method:	Parcel service

Construction

Colour temperature:	6000 K
Dimensions (WxDxH):	360 x 150 x 320 mm
Optical system:	Finite
Tube:	Monocular
Tube angle:	30°

KERN OBE 122

Elegant, dynamic and impressive - the new all-round compound microscope for schools, training and laboratories

KERN®



Piktogramme

STANDARD



OPTION



Power supply

Input voltage:	100 V - 240V AC 50/60Hz 0.3A
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO

Category

Brand:	Optics
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	435 x 380 x 275 mm
Gross weight:	5,500 kg
Net weight:	4,488 kg
Shipping method:	Parcel service

Construction

Colour temperature:	6000 K
Dimensions (WxDxH):	360 x 150 x 320 mm
Eye distance (max):	75
Eye distance (min):	48
Optical system:	Finite
Tube:	Binocular
Tube angle:	30°

KERN OBE124



Elegant, dynamic and impressive - the new all-round compound microscope for schools, training and laboratories



Piktogramme

STANDARD



OPTION



Power supply

Input voltage:	100 V - 240V AC 50/60Hz 0.3A
Mains adapter:	Mains adapter external
Mains adapter/adaptor included:	EURO

Category

Brand:	Optics
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	425 x 340 x 245 mm
Gross weight:	5,500 kg
Net weight:	4,488 kg
Shipping method:	Parcel service

Construction

Colour temperature:	6000 K
Dimensions (WxDxH):	360 x 150 x 320 mm
Eye distance (max):	75
Eye distance (min):	50
Optical system:	Finite
Rotation of tube 360°:	yes
Tube:	Trinocular
Tube angle:	30°

KERN OBE131



Elegant, dynamic and impressive - the new all-round compound microscope for schools, training and laboratories



Piktogramme

STANDARD



OPTION



Power supply

Input voltage:	100 V - 240V AC 50/60Hz 0.3A
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO

Category

Brand:	Optics
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	425 x 340 x 245 mm
Gross weight:	5,500 kg
Net weight:	4,488 kg
Shipping method:	Parcel service

Construction

Colour temperature:	6000 K
Dimensions (WxDxH):	360 x 150 x 320 mm
Optical system:	Finite
Tube:	Monocular
Tube angle:	30°

KERN OBE132



Elegant, dynamic and impressive - the new all-round compound microscope for schools, training and laboratories



Piktogramme

STANDARD



OPTION



Power supply

Input voltage:	100 V - 240V AC 50/60Hz 0.3A
Mains adapter:	Mains adapter external
Mains adapter/adaptor included:	EURO

Category

Brand:	Optics
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	425 x 340 x 245 mm
Gross weight:	5,500 kg
Net weight:	4,488 kg
Shipping method:	Parcel service

Construction

Colour temperature:	6000 K
Dimensions (WxDxH):	360 x 150 x 320 mm
Eye distance (max):	75
Eye distance (min):	48
Optical system:	Finite
Tube:	Binocular
Tube angle:	30°

KERN OBE134

Elegant, dynamic and impressive - the new all-round compound microscope for schools, training and laboratories

KERN®



Piktogramme

STANDARD



OPTION



Power supply

Input voltage:	100 V - 240V AC 50/60Hz 0.3A
Mains adapter:	Mains adapter external
Mains adapter/adaptor included:	EURO

Category

Brand:	Optics
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	425 x 340 x 245 mm
Gross weight:	5,500 kg
Net weight:	4,488 kg
Shipping method:	Parcel service

Construction

Colour temperature:	6000 K
Dimensions (WxDxH):	360 x 150 x 320 mm
Eye distance (max):	75
Eye distance (min):	50
Optical system:	Finite
Rotation of tube 360°:	yes
Tube:	Trinocular
Tube angle:	30°