

KERN CR 1000-3P1

Load cells made of stainless steel



Measuring system

| | |
|------------------------------------|---------|
| Combined Error: | 0,023 % |
| Load cell connection: | 4-wire |
| Nominal sensitivity: | 2 |
| OIML class: | C3 |
| Resolution Load cell â Verifiable: | 3000 e |
| Weighing capacity [Max]: | 1 t |
| Y value: | 10000 |

Environmental conditions

| | |
|--------------------------------|--------|
| Maximum operating temperature: | 70 °C |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -50 °C |
| Minimum operating temperature: | -10 °C |

Services (optional)

| | |
|--|----------|
| Factory calibration certificate (Pressure): | 961-264V |
|--|----------|

Category

| | |
|--------|--------|
| Brand: | Sauter |
|--------|--------|

Packaging & shipping

| | |
|-------------------------------|-------------------|
| Delivery: | 96 h |
| Dimensions packaging (WxDxH): | 220 x 220 x 80 mm |
| Gross weight: | 1,075 kg |
| Net weight: | 744 g |
| Shipping method: | Parcel service |

Construction

| | |
|---------------|-----|
| Cable length: | 3 m |
|---------------|-----|

Piktogramme

STANDARD



KERN CR 130-3P1

Load cells made of stainless steel



Measuring system

| | |
|------------------------------------|---------|
| Combined Error: | 0,023 % |
| Load cell connection: | 4-wire |
| Nominal sensitivity: | 1 |
| OIML class: | C3 |
| Resolution Load cell â Verifiable: | 3000 e |
| Weighing capacity [Max]: | 130 kg |
| Y value: | 10000 |

Environmental conditions

| | |
|--------------------------------|--------|
| Maximum operating temperature: | 70 °C |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -50 °C |
| Minimum operating temperature: | -10 °C |

Services (optional)

| | |
|--|----------|
| DAkkS Calibration certificate (Pressure): | 963-262V |
|--|----------|

Category

| | |
|--------|--------|
| Brand: | Sauter |
|--------|--------|

Packaging & shipping

| | |
|-------------------------------|-------------------|
| Delivery: | 96 h |
| Dimensions packaging (WxDxH): | 220 x 180 x 60 mm |
| Gross weight: | 598 g |
| Net weight: | 383 g |
| Shipping method: | Parcel service |

Construction

| | |
|---------------|-----|
| Cable length: | 3 m |
|---------------|-----|

Piktogramme

STANDARD



KERN CR 2000-3P1

Load cells made of stainless steel



Measuring system

| | |
|------------------------------------|---------|
| Combined Error: | 0,023 % |
| Load cell connection: | 4-wire |
| Nominal sensitivity: | 2 |
| OIML class: | C3 |
| Resolution Load cell â Verifiable: | 3000 e |
| Weighing capacity [Max]: | 2 t |
| Y value: | 10000 |

Environmental conditions

| | |
|--------------------------------|--------|
| Maximum operating temperature: | 70 °C |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -50 °C |
| Minimum operating temperature: | -10 °C |

Services (optional)

| | |
|--|----------|
| Factory calibration certificate (Pressure): | 961-264V |
|--|----------|

Category

| | |
|--------|--------|
| Brand: | Sauter |
|--------|--------|

Packaging & shipping

| | |
|-------------------------------|-------------------|
| Delivery: | 96 h |
| Dimensions packaging (WxDxH): | 220 x 220 x 85 mm |
| Gross weight: | 1,316 kg |
| Net weight: | 973 g |
| Shipping method: | Parcel service |

Construction

| | |
|---------------|-----|
| Cable length: | 6 m |
|---------------|-----|

Piktogramme

STANDARD



KERN CR 250-3P1

Load cells made of stainless steel



Measuring system

| | |
|------------------------------------|---------|
| Combined Error: | 0,023 % |
| Load cell connection: | 4-wire |
| Nominal sensitivity: | 1,750 |
| OIML class: | C3 |
| Resolution Load cell â Verifiable: | 3000 e |
| Weighing capacity [Max]: | 250 kg |
| Y value: | 10000 |

Environmental conditions

| | |
|--------------------------------|--------|
| Maximum operating temperature: | 70 °C |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -50 °C |
| Minimum operating temperature: | -10 °C |

Services (optional)

| | |
|--|----------|
| DAkkS Calibration certificate (Pressure): | 963-263V |
|--|----------|

Category

| | |
|--------|--------|
| Brand: | Sauter |
|--------|--------|

Packaging & shipping

| | |
|-------------------------------|-------------------|
| Delivery: | 96 h |
| Dimensions packaging (WxDxH): | 220 x 180 x 60 mm |
| Gross weight: | 881 g |
| Net weight: | 701 g |
| Shipping method: | Parcel service |

Construction

| | |
|---------------|-----|
| Cable length: | 3 m |
|---------------|-----|

Piktogramme

STANDARD



KERN CR500-3P1

Load cells made of stainless steel



Measuring system

| | |
|------------------------------------|---------|
| Combined Error: | 0,023 % |
| Load cell connection: | 4-wire |
| Nominal sensitivity: | 2 |
| OIML class: | C3 |
| Resolution Load cell â Verifiable: | 3000 e |
| Weighing capacity [Max]: | 500 kg |
| Y value: | 10000 |

Environmental conditions

| | |
|--------------------------------|--------|
| Maximum operating temperature: | 70 °C |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -50 °C |
| Minimum operating temperature: | -10 °C |

Services (optional)

| | |
|--|----------|
| DAkkS Calibration certificate (Pressure): | 963-263V |
|--|----------|

Category

| | |
|--------|--------|
| Brand: | Sauter |
|--------|--------|

Packaging & shipping

| | |
|-------------------------------|-------------------|
| Delivery: | 96 h |
| Dimensions packaging (WxDxH): | 220 x 180 x 60 mm |
| Gross weight: | 971 g |
| Net weight: | 799 g |
| Shipping method: | Parcel service |

Construction

| | |
|---------------|-----|
| Cable length: | 3 m |
|---------------|-----|

Piktogramme

STANDARD



KERN CR 60-3P1

Load cells made of stainless steel



Measuring system

| | |
|------------------------------------|---------|
| Combined Error: | 0,023 % |
| Load cell connection: | 4-wire |
| Nominal sensitivity: | 1 |
| OIML class: | C3 |
| Resolution Load cell â Verifiable: | 3000 e |
| Weighing capacity [Max]: | 60 kg |
| Y value: | 10000 |

Environmental conditions

| | |
|--------------------------------|--------|
| Maximum operating temperature: | 70 °C |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -50 °C |
| Minimum operating temperature: | -10 °C |

Services (optional)

| | |
|---|----------|
| DAkkS Calibration certificate (Pressure): | 963-262V |
|---|----------|

Category

| | |
|--------|--------|
| Brand: | Sauter |
|--------|--------|

Packaging & shipping

| | |
|-------------------------------|-------------------|
| Delivery: | 96 h |
| Dimensions packaging (WxDxH): | 220 x 180 x 60 mm |
| Gross weight: | 598 g |
| Net weight: | 383 g |
| Shipping method: | Parcel service |

Construction

| | |
|---------------|-----|
| Cable length: | 3 m |
|---------------|-----|

Piktogramme

STANDARD

