

KERN CR 1000-1Y1

Load cells made of alloyed steel

KERN®

Piktogramme

STANDARD



OPTION



Measuring system

Combined Error:	0,050 %
Load cell connection:	4-wire
Nominal sensitivity:	2
OIML class:	C1
Weighing capacity [Max]:	1 t

Environmental conditions

Maximum operating temperature:	65 °C
Minimum operating temperature:	-20 °C

Services (optional)

Factory calibration certificate (Pressure):	961-264V
Factory calibration certificate (Tensile):	961-164V
Factory calibration certificate (Tensile/Pressure):	961-364V

Category

Brand:	Sauter
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	200 x 165 x 135 mm
Gross weight:	1,835 kg
Net weight:	1,700 kg
Shipping method:	Parcel service

Construction

Cable length:	3 m
---------------	-----

KERN CR 10000-1Y1

Load cells made of alloyed steel

KERN®

Piktogramme

STANDARD



OPTION



Measuring system

Combined Error:	0,050 %
Load cell connection:	4-wire
Nominal sensitivity:	2
OIML class:	C1
Weighing capacity [Max]:	10 t

Environmental conditions

Maximum operating temperature:	65 °C
Minimum operating temperature:	-20 °C

Services (optional)

Factory calibration certificate (Pressure):	961-266V
Factory calibration certificate (Tensile):	961-166V
Factory calibration certificate (Tensile/Pressure):	961-366V

Category

Brand:	Sauter
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	200 x 165 x 135 mm
Gross weight:	1,835 kg
Net weight:	1,700 kg
Shipping method:	Parcel service

Construction

Cable length:	3 m
---------------	-----

KERN CR 20000-1Y1

Load cells made of alloyed steel



Measuring system

Combined Error:	0,050 %
Load cell connection:	4-wire
Nominal sensitivity:	2
OIML class:	C1
Weighing capacity [Max]:	20 t

Environmental conditions

Maximum operating temperature:	65 °C
Minimum operating temperature:	-20 °C

Category

Brand:	Sauter
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	200 x 165 x 135 mm
Gross weight:	1,835 kg
Net weight:	1,700 kg
Shipping method:	Parcel service

Construction

Cable length:	3 m
---------------	-----

Piktogramme

STANDARD



OPTION



KERN CR500-1Y1

Load cells made of alloyed steel

Piktogramme

STANDARD



OPTION



Measuring system

Combined Error:	0,050 %
Load cell connection:	4-wire
Nominal sensitivity:	2
OIML class:	C1
Weighing capacity [Max]:	500 kg

Environmental conditions

Maximum operating temperature:	65 °C
Minimum operating temperature:	-20 °C

Services (optional)

DAkkS Calibration certificate (Pressure):	963-263V
DAkkS Calibration certificate (Tensile):	963-163V
DAkkS Calibration certificate (Tensile/Pressure):	963-363V

Category

Brand:	Sauter
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	200 x 165 x 135 mm
Gross weight:	1,835 kg
Net weight:	1,700 kg
Shipping method:	Parcel service

Construction

Cable length:	3 m
---------------	-----

KERN CR5000-1Y1

Load cells made of alloyed steel

KERN®

Piktogramme

STANDARD



OPTION



Measuring system

Combined Error:	0,050 %
Load cell connection:	4-wire
Nominal sensitivity:	2
OIML class:	C1
Weighing capacity [Max]:	5 t

Environmental conditions

Maximum operating temperature:	65 °C
Minimum operating temperature:	-20 °C

Services (optional)

Factory calibration certificate (Pressure):	961-265V
Factory calibration certificate (Tensile):	961-165V
Factory calibration certificate (Tensile/Pressure):	961-365V

Category

Brand:	Sauter
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	200 x 165 x 135 mm
Gross weight:	1,835 kg
Net weight:	1,700 kg
Shipping method:	Parcel service

Construction

Cable length:	3 m
---------------	-----