# KERN CO10-Y1





Measuring system	
Combined Error:	0,500 %
Load cell connection:	4-wire
Nominal sensitivity:	1
OIML class:	G5
Weighing capacity [Max]:	10 kg
Environmental conditions	
Maximum operating temperature:	40 °C
Minimum operating temperature:	O°C
Services (optional)	
DAkkS Calibration certificate	963-261V
(Pressure):	
Category	
Brand:	Sauter
Dockoging & chipping	
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	120 x 90 x 85 mm
Gross weight:	95 g
Net weight:	49 g
Shipping method:	Parcel service
Construction	
Cable length:	2 m

# KERN CO100-Y1





0,500 %
4-wire
1
G5
100 kg
40 °C
0°C
963-262V
Sauter
24 h
120 x 90 x 85 mm
96 g
49 g
Parcel service

# KERN CO1000-Y1





Measuring system	
Combined Error:	0,500 %
Load cell connection:	4-wire
Nominal sensitivity:	1
OIML class:	G5
Weighing capacity [Max]:	1 t
Environmental conditions	
Maximum operating temperature:	40 °C
Minimum operating temperature:	O°O
Services (optional)	
Factory calibration certificate (Pressure):	961-264V
Category	
Brand:	Sauter
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	120 x 90 x 85 mm
Gross weight:	119 g
Net weight:	73 g
Shipping method:	Parcel service
Construction	
Cable length:	2 m

# KERN CO20-Y1





Measuring system	
Combined Error:	0,500 %
Load cell connection:	4-wire
Nominal sensitivity:	1
OIML class:	G5
Weighing capacity [Max]:	20 kg
Environmental conditions	
Maximum operating temperature:	40 °C
Minimum operating temperature:	O°O
Services (optional)	
DAkkS Calibration certificate	963-261V
(Pressure):	
Category	
Brand:	Sauter
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	120 x 90 x 85 mm
Gross weight:	95 g
Net weight:	49 g
Shipping method:	Parcel service
Construction	
Cable length:	2 m

# KERN CO200-Y1





Measuring system	
Combined Error:	0,500 %
Load cell connection:	4-wire
Nominal sensitivity:	1,500
OIML class:	G5
Weighing capacity [Max]:	200 kg
Environmental conditions	
Maximum operating temperature:	40 °C
Minimum operating temperature:	O°O
Services (optional)	
DAkkS Calibration certificate (Pressure):	963-262V
Category	
Category Brand:	Sauter
	Sauter
Brand:	Sauter 24 h
Brand: Packaging & shipping	
Brand: Packaging & shipping Delivery:	24 h
Brand: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	24 h 120 x 90 x 85 mm
Brand: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	24 h 120 x 90 x 85 mm 92 g
Brand: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	24 h 120 x 90 x 85 mm 92 g 49 g
Brand: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	24 h 120 x 90 x 85 mm 92 g 49 g

# KERN CO 2000-Y1





Measuring system	
Combined Error:	0,500 %
Load cell connection:	4-wire
Nominal sensitivity:	1
OIML class:	G5
Weighing capacity [Max]:	2 t
Environmental conditions	
Maximum operating temperature:	40 °C
Minimum operating temperature:	O°O
Services (optional)	
Factory calibration certificate (Pressure):	961-264V
Category	
Brand:	Sauter
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	120 x 90 x 85 mm
Gross weight:	145 g
Net weight:	97 g
Shipping method:	Parcel service
Construction	
Cable length:	2 m

# KERN CO50-Y1





Measuring system	
Combined Error:	0,500 %
Load cell connection:	4-wire
Nominal sensitivity:	1,500
OIML class:	G5
Weighing capacity [Max]:	50 kg
Environmental conditions	
Maximum operating temperature:	40 °C
Minimum operating temperature:	O°C
Services (optional)	
DAkkS Calibration certificate (Pressure):	963-261V
Category	
Brand:	Sauter
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	120 x 90 x 85 mm
Gross weight:	95 g
Net weight:	49 g
Shipping method:	Parcel service
Construction	
Construction Cable length:	2 m

# KERN CO500-Y1





Measuring system	
Combined Error:	0,500 %
Load cell connection:	4-wire
Nominal sensitivity:	1,500
OIML class:	G5
Weighing capacity [Max]:	500 kg
Environmental conditions	
Maximum operating temperature:	40 °C
Minimum operating temperature:	0°C
Services (optional)	
DAkkS Calibration certificate (Pressure):	963-263V
Category	
Brand:	Sauter
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	120 x 90 x 85 mm
Gross weight:	119 g
Net weight:	73 g
Shipping method:	Parcel service
Construction	
Construction Cable length:	2 m