

Mobile ultrasound hardness testing device SAUTER HO-M



Premium UCI hardness testing device for Rockwell, Brinell and Vickers with a motorised sensor for automated measurement processes

Features

- This range has **identical product features as SAUTER HO range**, but is fitted with a **motorised sensor for automated measurement processes** instead of the manual probe
- **1** The motorised sensor has got a magnetic support ring, which fixes the sensor on the test object in a safe way. For non-magnetic test items, the motorised sensor can be easily fixed by hand using an ergonomically-shaped support ring
- A motor inside the probe independently takes on the process of pressing the indenter into the test item, which helps to minimise incorrect use by the operator
- **2 One-button function:** the measurement process can be started with a single keypress. By this particularly easy operation, the user can carry out most demanding hardness tests without a longer training period.
- Virtually non-destructive testing: the resulting penetrations can only be seen under a microscope
- **Short duration of measurement:** only 2 seconds
- **Higher accuracy and repeatability** than with manual probes
- **Particularly suitable for small, thin parts** thanks to the automated testing procedure
- **Designed for parts with hardened surfaces**, because of the low penetration depth of the indenter
- Scope of supply: 1 display device, 1 motorised sensor, 1 transport case, 1 connection cable sensor/display device, 1 USB cable, 1 hardness comparison plate, 1 power supply (EU), 1 Allen key, software to transfer the saved data to a PC

Accessories

- **3 Test stand** for round, flat objects for use with these motorised sensors: HO-A15 to -A18. This test stand is ideal for hardness testing of round objects such as **4** pipes or rods up from \varnothing 80 mm. Its lightweight aluminium construction enables a fatigue-free operation. The precise adjustment of the sensor position and the use of motorised sensors enables a very fast working procedure. Net weight approx. 1.6 kg, overall dimensions WxDxH 205x142x284mm, SAUTER HO-A19
- **Motorised sensor** as an accessory for models in the SAUTER HO range
 Test force 0,3 N, HO-A15
 Test force 0,5 N, HO-A16
 Test force 0,8 N, HO-A17
 Test force 1 N, HO-A18
- **Display device**, as standard, can be reordered, SAUTER HO-A03
- **5 Transport case with standard accessories** for operation with a motorised sensor, as standard, can be reordered, SAUTER HO-A21

STANDARD





































OPTION



Model	Hardness scale	Test force	Attachment ring \varnothing mm	Sensor length mm	Min. weight of test item g	Min. thickness of test item mm	Option	
							Factory calibration certificates	
SAUTER		N					KERN	
HO 3M	HV 0,3	0,3	46	198	300	2	961-270	
HO 5M	HV 0,5	0,5	46	198	300	2	961-270	
HO 8M	HV 0,8	0,8	46	198	300	2	961-270	
HO 10M	HV 1	1	46	198	300	2	961-270	

Pictograms

 Adjusting program (CAL): For quick setting of the instrument's accuracy. External adjusting weight required.	 Control outputs (optocoupler, digital I/O): to connect relays, signal lamps, valves, etc.	 ZERO: Resets the display to "0".
 Calibration block: standard for adjusting or correcting the measuring device.	 Analogue interface: to connect a suitable peripheral device for analogue processing of the measurements	 Battery operation: Ready for battery operation. The battery type is specified for each device.
 Peak hold function: capturing a peak value within a measuring process.	 Statistics: using the saved values, the device calculates statistical data, such as average value, standard deviation etc.	 Rechargeable battery pack: rechargeable set.
 Scan mode: continuous capture and display of measurements.	 PC Software: to transfer the measurement data from the device to a PC.	 Mains adapter: 230V/50Hz in standard version for EU. On request GB, AUS or USA version available.
 Push and Pull: the measuring device can capture tension and compression forces.	 Printer: a printer can be connected to the device to print out the measurement data.	 Power supply: Integrated, 230V/50Hz in EU. More standards e.g. GB, AUS or USA on request.
 Length measurement: captures the geometric dimensions of a test object or the movement during a test process.	 Network interface: For connecting the scale to an Ethernet network.	 Motorised drive: The mechanical movement is carried out by a electric motor.
 Focus function: increases the measuring accuracy of a device within a defined measuring range.	 KERN Communication Protocol (KCP): It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems.	 Motorised drive: The mechanical movement is carried out by a synchronous motor (stepper).
 Internal memory: to save measurements in the device memory.		 Fast-Move: the total length of travel can be covered by a single lever movement.
 Data interface RS-232: bidirectional, for connection of printer and PC.	 GLP/ISO record keeping: of measurement data with date, time and serial number. Only with SAUTER printers	 DAkkS calibration possible: The time required for DAkkS calibration is shown in days in the pictogram.
 Data interface USB: To connect the measuring instrument to a printer, PC or other peripheral devices.	 Measuring units: Weighing units can be switched to e.g. non-metric at the touch of a key. Please refer to website for more details.	 Factory calibration: The time required for factory calibration is specified in the pictogram.
 WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals.	 Measuring with tolerance range (limit-setting function): Upper and lower limiting can be programmed individually. The process is supported by an audible or visual signal, see the relevant model	 Package shipment: The time required for internal shipping preparations is shown in days in the pictogram.
 Data interface Infrared: To transfer data from the measuring instrument to a printer, PC or other peripheral devices.		 Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram.

Your KERN specialist dealer: